

According to the New Recreational Craft Directive 2013/53/EU, B+F Module, notified body n°0607

Modern and timeless, Sécu 12 remains the reference workboat for yacht clubs and firefighters since nearly 30 years.




1



2



3



Specifications

Double rotomoulded hull	
Design category – D	
5 passengers: 375 kg load (distributed)	
Passengers + equipment: 430 kg load	
Design category – C	
2 passengers: 150 kg load (distributed)	
Passengers + equipment: 200 kg load	
Maximum outboard engine:	
25 HP i.e. 18,7 kW outboard	
Short shaft / maximum weight: 70 kg	
Recommended: 9,9 HP i.e. 7,4 kW	
Over-all length:	3,60 m
Over-all breadth:	1,50 m
Depth:	0,44 m
Weight (without load):	100 kg

> NEVER EXCEED MAXIMUM LOAD

Standard equipment

- Engine panel
- Storage bench 90 litres **1**
- Mooring ring
- Chromed drain plug **2**
- Mooring cleat **3**
- Deck lashing

Options

- Sockets for rowlocks
- Oars
- Console
- Storage bench 90 litres
- Tank locker (type B)

Partition table

C		D	
adult 75 kg	child 37,5 kg	adult 75 kg	child 37,5 kg
2	+	0	
1	+	2	
		5	+
		4	+
		3	+
		2	+
		1	+
		0	
		2	
		4	
		6	
		8	

